

TECHNICAL CARD LAMELIO SKIRTING BOARDS

MATERIAL

Extruded polystyrene (XPS)

COLLECTIONS AND DIMENSIONS

| Collection | Index | Dimensions (W × D × L) |
|------------|--------------|------------------------|
| | | |
| ESSENZA S | LP-ESSENZA S | 60x14x2000mm |
| ESSENZA M | LP-ESSENZA M | 80x14x2000mm |
| ESSENZA L | LP-ESSENZA L | 100x14x2000mm |
| ARCHE S | LP-ARCHE S | 60x14x2000mm |
| ARCHE M | LP-ARCHE M | 80x14x2000mm |
| ARCHE L | LP-ARCHE L | 100x14x2000mm |
| LINEA M | LP-LINEA M | 80x15x2000mm |
| LINEA L | LP-LINEA L | 100x15x2000mm |
| QUADRO M | LP-QUADRO M | 80x15x2000mm |
| QUADRO L | LP-QUADRO L | 100x15x2000mm |
| STELLA M | LP-STELLA M | 80x13,5x2000mm |
| STELLA L | LP-STELLA L | 100x13,5x2000mm |
| | | |

PRODUCT FEATURES

- Made of lightweight, durable, and moisture-resistant XPS material.
- Impact- and scratch-resistant.
- Designed for indoor use.
- Available in various profiles classic, modern, and minimalist.
- 100% recyclable product.



TECHNICAL CARD LAMELIO SKIRTING BOARDS

INSTALLATION RECOMMENDATIONS

- Install using mounting adhesive (e.g., Lamelio adhesive or another polymer hybrid adhesive free of solvents and isocyanates).
- Apply on a smooth, clean, and dry surface ensuring proper adhesion.
- Skirting boards can be cut using a hand saw, jigsaw, or miter saw.
- For corners, a 45-degree miter cut should be used.

Before installation, allow the boards to acclimatize

· in the room where they will be installed.

CARE AND CLEANING

- Clean with a soft, damp microfiber cloth.
- Do not use strong detergents, bleach, solvents, or abrasive products.
- After cleaning, wipe the surface thoroughly with a dry cloth.
- Leaving cleaning agents on the surface may cause discoloration.

PAINTING

Lamelio skirting boards can be painted with acrylic or latex paints.

Before painting, the surface should be cleaned, degreased, and primed for better paint adhesion.

Painting can be done:

- by spraying for a perfectly smooth finish,
- with a brush or roller using a high-coverage acrylic paint (1–2 coats recommended).

The use of solvent-based paints is not recommended.

STORAGE AND TRANSPORT

- Store in a dry place, laid flat on an even surface.
- · Protect from direct sunlight and heat sources.
- Avoid bending or crushing the boards during transport and storage.